
40 C.F.R. § 60.274

Monitoring of operations.

(a) The owner or operator subject to the provisions of this subpart shall maintain records daily of the following information:

(1) Time and duration of each charge;

(2) Time and duration of each tap;

(3) All flow rate data obtained under paragraph (b) of this section, or equivalent obtained under paragraph (d) of this section; and

(4) All pressure data obtained under paragraph (f) of this section.

(b) Except as provided under paragraph (d) of this section, the owner or operator subject to the provisions of this subpart shall:

(1) Monitor and record on a continuous basis the rolling 15-minute average furnace static pressure (if a DEC system is in use, and a furnace static pressure gauge is installed according to paragraph (f) of this section) and either:

(i) Install, calibrate, and maintain a monitoring device that continuously records the capture system fan motor amperes and damper position(s);

(ii) Install, calibrate, and maintain a monitoring device that continuously records on a rolling 15-minute average basis either the volumetric flow rate through each separately ducted hood; or

(iii) Install, calibrate, and maintain a monitoring device that continuously records the volumetric flow rate at the control device inlet and continuously record damper position(s).

(2) The volumetric flow monitoring device(s) may be installed in any appropriate location in the capture system such that reproducible flow rate monitoring will result. The flow rate monitoring device(s) shall have an accuracy of ± 10 percent over its normal operating range and shall be calibrated according to the manufacturer's instructions. The Administrator may require the owner or operator to demonstrate the accuracy of the monitoring device(s) relative to EPA Methods 1 and 2 of appendix A of this part.

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)