
40 C.F.R. § 60.274a

Monitoring of operations.

(a) The owner or operator subject to the provisions of this subpart shall maintain records of the following information:

- (1) All data obtained under paragraph (b) of this section; and
- (2) All monthly operational status inspections performed under paragraph (c) of this section.

(b) Except as provided under paragraph (e) of this section, the owner or operator subject to the provisions of this subpart shall:

(1) Monitor and record once per shift the block 15-minute average furnace static pressure (if a DEC system is in use, and a furnace static pressure gauge is installed according to paragraph (f) of this section) and either:

(i) Install, calibrate, and maintain a monitoring device that continuously records the capture system fan motor amperes and damper position(s);

(ii) Monitor and record as no greater than 15-minute integrated block average basis the volumetric flow rate through each separately ducted hood; or

(iii) Install, calibrate, and maintain a monitoring device that continuously records the volumetric flow rate at the control device inlet and record damper positions(s).

(2) The volumetric flow monitoring device(s) may be installed in any appropriate location in the capture system such that reproducible flow rate monitoring will result. The flow rate monitoring device(s) shall have an accuracy of ± 10 percent over its normal operating range and shall be calibrated according to the manufacturer's instructions. The Administrator may require the owner or operator to demonstrate the accuracy of the monitoring device(s) relative to EPA Methods 1 and 2 of appendix A of this part.

(3) Parameters monitored pursuant to this paragraph, excluding damper position, shall be recorded as integrated block averages not to exceed 15 minutes.

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)