

---

## 40 C.F.R. § 60.276a

---

### Recordkeeping and reporting requirements.

---

- (a) Records of the measurements required in § 60.274a must be retained for at least 5 years following the date of the measurement.
- (b) Each owner or operator shall submit a written report of exceedances of the control device opacity to the Administrator or delegated authority semi-annually. For the purposes of these reports, exceedances are defined as all 6-minute periods during which the average opacity of emissions from the control device is 3 percent or greater.
- (c) Continuous operation at a furnace static pressure that exceeds the operational range or control setting under § 60.274a(g), for owners and operators that elect to install a furnace static pressure monitoring device under § 60.274a(f) and either operation of control system fan motor amperes at values exceeding ±15 percent of the value established under § 60.274a(c) or operation at flow rates lower than those established under § 60.274a(c) may be considered by the Administrator or delegated authority to be unacceptable operation and maintenance of the affected facility. Operation at such values shall be reported to the Administrator or delegated authority semiannually.
- (d) The requirements of this section remain in force until and unless EPA, in delegating enforcement authority to a State under section 111(c) of the Act, approves reporting requirements or an alternative means of compliance surveillance adopted by such State. In that event, affected sources within the State will be relieved of the obligation to comply with this section, provided that they comply with the requirements established by the State.
- (e) When the owner or operator of an EAF or AOD is required to demonstrate compliance with the standard under § 60.275a(b)(2) or a combination of § 60.275a(b)(1) and (b)(2) the owner or operator shall provide notice to the Administrator or delegated authority of the procedure(s) that will be used to determine compliance. Notification of the procedure(s) to be used must be postmarked at least 30 days prior to the performance test.
- (f) For the purpose of this subpart, the owner or operator shall conduct the demonstration of compliance with § 60.272a(a) of this subpart and furnish the Administrator or delegated authority with a written report of the results of the test. This report shall include the following information:
- (1) Facility name and address;
  - (2) Plant representative;
  - (3) Make and model of the control device, and continuous opacity monitoring equipment, if applicable;
  - (4) Flow diagram of process and emission capture system including other equipment or process(es) ducted to the same control device;

- (5) Rated (design) capacity of process equipment;
- (6) Those data required under § 60.274a(h) of this subpart;
- (i) List of charge and tap weights and materials;
- (ii) Heat times and process log;
- (iii) Control device operation log; and
- (iv) Continuous opacity monitor or EPA Method 9 data, or, as an alternative to EPA Method 9, according to ASTM D7520-16 (incorporated by reference, see § 60.17), with the caveats described under *Shop opacity* in § 60.271.

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)