

40 C.F.R. § 60.58c

Reporting and recordkeeping requirements.

- (a) The owner or operator of an affected facility shall submit notifications, as provided by § 60.7. In addition, the owner or operator shall submit the following information:
- (1) Prior to commencement of construction;
- (i) A statement of intent to construct;
- (ii) The anticipated date of commencement of construction; and
- (iii) All documentation produced as a result of the siting requirements of § 60.54c.
 - (2) Prior to initial startup;
- (i) The type(s) of waste to be combusted;
- (ii) The maximum design waste burning capacity;
- (iii) The anticipated maximum charge rate; and
- (iv) If applicable, the petition for site-specific operating parameters under § 60.56c(j).
 - (b) The owner or operator of an affected facility shall maintain the following information (as applicable) for a period of at least 5 years:
 - (1) Calendar date of each record;
 - (2) Records of the following data:
- (i) Concentrations of any pollutant listed in § 60.52c or measurements of opacity as determined by the continuous emission monitoring system (if applicable);
- (ii) Results of fugitive emissions (by EPA Reference Method 22) tests, if applicable;
- (iii) HMIWI charge dates, times, and weights and hourly charge rates;
- (iv) Fabric filter inlet temperatures during each minute of operation, as applicable;
- (v) Amount and type of dioxin/furan sorbent used during each hour of operation, as applicable;
- (vi) Amount and type of Hg sorbent used during each hour of operation, as applicable;
- (vii) Amount and type of HCl sorbent used during each hour of operation, as applicable;

- (viii) For affected facilities as defined in § 60.50c(a)(3) and (4), amount and type of NO_X reagent used during each hour of operation, as applicable;
- (ix) Secondary chamber temperatures recorded during each minute of operation;
- (x) Liquor flow rate to the wet scrubber inlet during each minute of operation, as applicable;
- (xi) Horsepower or amperage to the wet scrubber during each minute of operation, as applicable;
- (xii) Pressure drop across the wet scrubber system during each minute of operation, as applicable,

This document is only available to subscribers. Please log in or purchase access.

Purchase Login