

# 40 C.F.R. § 420.104

## New source performance standards (NSPS).

The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the standards set forth below.

(a) *Cold rolling mills—(1) Recirculation—single stand.*

### Subpart J

Pollutant or pollutant property	New source performance standards	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (pounds per 1,000 lb) of product	
TSS	0.00125	0.000626
O&G	0.000522	0.000209
Chromium <sup>1</sup>	0.0000209	0.0000084
Lead	0.0000094	0.0000031
Nickel <sup>1</sup>	0.0000188	0.0000063
Zinc	0.0000063	0.0000021
Naphthalene	0.0000021	
Tetrachloroethylene	0.0000031	
pH	( 2 )	( 2 )

<sup>1</sup> The limitations for chromium and nickel shall be applicable in lieu of those for lead and zinc when cold rolling wastewaters are cotreated with descaling or combination acid pickling wastewaters.

<sup>2</sup> Within the range of 6.0 to 9.0.

(2) *Recirculation—multiple stands.*

### Subpart J

Pollutant or pollutant property	New source performance standards
---------------------------------	----------------------------------

	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kgg (pounds per 1,000 lb) of product	
TSS	0.00250	0.00125
O&G	0.00104	0.000417
Chromium 1	0.0000418	0.0000167
Lead	0.0000188	0.0000063
Nickel 1	0.0000376	0.0000125
Zinc	0.0000125	0.0000042
Naphthalene	0.0000042	
Tetrachloroethylene	0.0000063	
pH	( 2)	( 2)

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)