

40 C.F.R. § 421.106

Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources. The mass of wastewater pollutants in primary tungsten process wastewater introduced into a POTW shall not exceed the following values:

(a) Subpart J—Tungstic Acid Rinse.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of tungstic acid (as W) produced	
Lead	11.490	5.333
Zinc	41.850	17.230
Ammonia (as N)	5,469.000	2,404.000

(b) Subpart J—Acid Leach Wet Air Pollution Control.

PSNS

Pollutant or pollutant property	Maximum for any one day	Maximum for monthly average
	mg/kg (pounds per million) of tungstic acid (as W) produced	
Lead	1.003	0.466
Zinc	3.653	1.504
Ammonia (as N)	477.400	209.900

(c) Subpart J—Alkali Leach Wash.

PSNS

Pollutant or pollutant property	Maximum for any one day	Maximum for monthly average
	mg/kg (pounds per million) of sodium tungstate (as W) produced	

Lead	0.000	0.000
Zinc	0.000	0.000
Ammonia (as N)	0.000	0.000

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)