

40 C.F.R. § 421.112

Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Subpart K—Concentrate Digestion Wet Air Pollution Control.

BPT Effluent Limitations

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of concentrate digested	
Lead	2.612	1.244
Zinc	9.080	3.794
Ammonia (as N)	829.000	364.500
Fluoride	217.700	124.400
Total suspended solids	255.000	121.300
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Subpart K—Solvent Extraction Raffinate.

BPT Effluent Limitations

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of concentrate digested	
Lead	3.888	1.851
Zinc	13.520	5.647
Ammonia (as N)	1,233.000	542.500

Fluoride	324.000	185.100
Total Suspended Solids	379.500	189.500
pH	(1)	(1)

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)