

40 C.F.R. § 421.132

Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Subpart M— Battery Cracking

BPT Effluent Limitations

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead scrap produced	
Antimony	1.932	.862
Arsenic	1.407	.579
Lead	.283	.135
Zinc	.983	.411
Ammonia (as N)	.000	.000
Total suspended solids	27.600	13.130
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Subpart M— Blast, Reverberatory, or Rotary Furnace Wet Air Pollution Control

BPT Effluent Limitations

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead produced from smelting	
Antimony	7.491	3.341
Arsenic	5.455	2.245

Lead	1.096	.522
Zinc	3.811	1.592
Ammonia (as N)	.000	.000
Total suspended solids	107.000	50.900
pH	(1)	(1)

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)