

# 40 C.F.R. § 421.134

## Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Subpart M—Battery Cracking.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead scrap produced	
Antimony	1.299	.579
Arsenic	.936	.384
Lead	.189	.087
Zinc	.687	.283
Ammonia (as N)	.000	.000
Total suspended solids	10.100	8.076
pH	(1)	(1)

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(b) Subpart M—Blast, Reverberatory, or Rotary Furnace Wet Air Pollution Control.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead produced from smelting	
Antimony	5.038	2.245
Arsenic	3.628	1.488
Lead	.731	.339
Zinc	2.662	1.096

Ammonia (as N)	0.000	0.000
Total suspended solids	39.150	31.320
pH	(1)	(1)

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)