

# 40 C.F.R. § 421.292

## Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Tin smelter SO<sub>2</sub> scrubber.

### BPT Limitations for the Secondary Tin Subcategory

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of crude tapped tin metal produced	
Arsenic	19.220	8.554
Lead	3.863	1.840
Iron	11.040	5.611
Tin	3.495	2.024
Total suspended solids	377.100	179.400
pH	(1)	(1)

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(b) Dealuminizing rinse.

### BPT Limitations for the Secondary Tin Subcategory

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of dealuminized scrap produced	
Lead	0.015	0.007
Cyanide (total)	0.010	0.004
Fluoride	1.225	0.700

Tin	0.013	0.008
Total suspended solids	1.435	0.683
pH	(1)	(1)

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)