

# 40 C.F.R. § 421.303

## Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Chlorination off-gas wet air pollution control.

### BAT Limitations for the Primary and Secondary Titanium Subcategory

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of TiCl <sub>4</sub> produced	
Chromium (total)	0.346	0.140
Lead	0.262	0.122
Nickel	0.515	0.346
Titanium	0.496	0.215

(b) Chlorination area-vent wet air pollution control.

### BAT Limitations for the Primary and Secondary Titanium Subcategory

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of TiCl <sub>4</sub> produced	
Chromium (total)	0.385	0.156
Lead	0.291	0.135
Nickel	0.572	0.385
Titanium	0.551	0.239

(c) TiCl<sub>4</sub> handling wet air pollution control.

### BAT Limitations for the Primary and Secondary Titanium Subcategory

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of TiCl <sub>4</sub> handled	
Chromium (total)	0.069	0.028
Lead	0.052	0.024
Nickel	0.103	0.069
Titanium	0.099	0.043

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)