
40 C.F.R. § 421.74

Standards of performance for new sources.

Any new source subject to this subpart must achieve the following performance standards:

(a) Subpart G—Sinter Plant Materials Handling Wet Air Pollution Control.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per billion pounds) of sinter production	
Lead	.000	.000
Zinc	.000	.000
Total suspended solids	.000	.000
pH	(1)	(1)

¹Within the range of 7.5 to 10.0 at all times.

(b) Subpart G—Blast Furnace Wet Air Pollution Control.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per billion pounds) of blast furnace lead bullion produced	
Lead	.000	.000
Zinc	.000	.000
Total suspended solids	.000	.000
pH	(1)	(1)

¹Within the range of 7.5 to 10.0 at all times.

(c) Subpart G—Blast Furnace Slag Granulation.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per billion pounds) of blast furnace lead bullion produced	
Lead	.000	.000
Zinc	.000	.000
Total suspended solids	.000	.000
pH	(1)	(1)

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)