

40 C.F.R. § 423.17

Pretreatment standards for new sources (PSNS).

- (a) 1982 PSNS. Except as provided in 40 CFR 403.7, any new source as of October 14, 1980, subject to paragraph (a) of this section, which introduces pollutants into a publicly owned treatment works, must comply with 40 CFR part 403, the following pretreatment standards for new sources, and the PSES in § 423.16, established on November 3, 2015. In the case of conflict, the more stringent standards apply:
- (1) *PCBs*. There shall be no discharge of polychlorinated biphenyl compounds such as those used for transformer fluid.
- (2) *Chemical metal cleaning wastes.* The pollutants discharged in chemical metal cleaning wastes shall not exceed the concentration listed in the following table:

Pollutant or pollutant property	PSNS
	Maximum for any 1 day (mg/L)
Copper, total	1.0

(3) [Reserved]

(4)

(i) *Cooling tower blowdown.* The pollutants discharged in cooling tower blowdown shall not exceed the concentration listed in the following table:

Pollutant or pollutant property	PSNS
	Maximum for any time (mg/L)
The 126 priority pollutants (appendix A) contained in chemicals added for cooling tower maintenance, except:	(1)
Chromium, total	0.2
zinc, total	1.0

This document is only available to subscribers. Please log in or purchase access.

Purchase Login