

# 40 C.F.R. § 430.22

## Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

### Subpart B

[BPT effluent limitations for bleached kraft facilities where market pulp is produced]

Pollutant or pollutant parameter	Kg/kkg (or pounds per 1,000 lb) of product		
	Continuous dischargers		Non-continuous dischargers (annual average)
	Maximum for any 1 day	Average of daily values for 30 consecutive days	
BOD <sub>5</sub>	15.45	8.05	4.52
TSS	30.4	16.4	9.01
pH	(1)	(1)	(1)

<sup>1</sup> Within the range of 5.0 to 9.0 at all times.

### Subpart B

[BPT effluent limitations for bleached kraft facilities where paperboard, coarse paper, and tissue paper are produced]

Pollutant or pollutant parameter	Kg/kkg (or pounds per 1,000 lb) of product		
	Continuous dischargers		Non-continuous dischargers (annual average)
	Maximum for any 1 day	Average of daily values for 30 consecutive days	
BOD <sub>5</sub>	13.65	7.1	3.99

TSS	24.0	12.9	7.09
pH	(1)	(1)	(1)

<sup>1</sup> Within the range of 5.0 to 9.0 at all times.

Subpart B

[BPT effluent limitations for bleached kraft facilities where pulp and fine papers are produced]

Pollutant or pollutant parameter	Kg/kkg (or pounds per 1,000 lb) of product		
	Continuous dischargers		Non-continuous dischargers (annual average)
	Maximum for any 1 day	Average of daily values for 30 consecutive days	
BOD <sub>5</sub>	10.6	5.5	3.09
TSS	22.15	11.9	6.54
pH	(1)	(1)	(1)

<sup>1</sup> Within the range of 5.0 to 9.0 at all times.

Subpart B

[BPT effluent limitations for soda facilities where pulp and paper are produced]

Pollutant or pollutant parameter	Kg/kkg (or pounds per 1,000 lb) of product		
	Continuous dischargers		Non-continuous dischargers (annual average)
	Maximum for any 1 day	Average of daily values for 30 consecutive days	
BOD <sub>5</sub>	13.7	7.1	3.99
TSS	24.5	13.2	7.25
pH	(1)	(1)	(1)

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)