

40 C.F.R. § 430.25

New source performance standards (NSPS).

New sources subject to this subpart must achieve the following new source performance standards (NSPS), as applicable.

(a) The following standards apply to each new source that commenced discharge after June 15, 1988 and before June 15, 1998, provided that the new source was constructed to meet these standards:

Subpart B

[1982 New Source Performance Standards for bleached kraft facilities where market pulp is produced]

Pollutant or pollutant property	Continuous dischargers		Non-continuous dischargers
	Maximum for any 1 day	Average of daily values for 30 consecutive days	Annual average
	kg/kkg (or pounds per 1,000 lb) of product		
BOD ₅	10.3	5.5	2.88
TSS	18.2	9.5	5.00
pH	(1)	(1)	(1)

¹ Within the range of 5.0 to 9.0 at all times.

Subpart B

[1982 New Source Performance Standards for bleached kraft facilities where paperboard, coarse paper, and tissue paper are produced]

Pollutant or pollutant property	Continuous dischargers		Non-continuous dischargers
	Maximum for any 1 day	Average of daily values for 30 consecutive days	Annual average
	kg/kkg (or pounds per 1,000 lb) of product		
BOD ₅	8.5	4.6	2.41
TSS	14.6	7.6	4.00

pH	(1)	(1)	(1)
----	-----	-----	-----

¹ Within the range of 5.0 to 9.0 at all times.

Subpart B

[1982 New Source Performance Standards for bleached kraft facilities where pulp and fine papers are produced and soda facilities where pulp and paper are produced]

Pollutant or pollutant property	Continuous dischargers		Non-continuous dischargers
	Maximum for any 1 day	Average of daily values for 30 consecutive days	Annual average
	kg/kkg (or pounds per 1,000 lb) of product		
BOD ₅	5.7	3.1	1.62
TSS	9.1	4.8	2.53
pH	(1)	(1)	(1)

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)