

40 C.F.R. § 435.14

Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30–32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT):

BCT Effluent Limitations

Waste source	Pollutant parameter	BCT effluent limitation
Produced water	Oil & grease	The maximum for any one day shall not exceed 72 mg/l; the average of values for 30 consecutive days shall not exceed 48 mg/l.
Drilling fluids and drill cuttings:		
(A) For facilities located within 3 miles from shore		No discharge. ¹
(B) For facilities located beyond 3 miles from shore:		
Water-based drilling fluids and associated drill cuttings	Free Oil	No discharge. ²
Non-aqueous drilling fluids		No discharge.
Drill cuttings associated with non-aqueous drilling fluids	Free Oil	No discharge. ²
Well treatment, completion and workover fluids	Free oil	No discharge. ²
Deck drainage	Free oil	No discharge. ³
Produced sand		No discharge.
Sanitary M10	Residual chlorine	Minimum of 1 mg/l and maintained as close to this concentration as possible.
Sanitary M91M	Floating solids	No discharge.

Domestic Waste	Floating solids	No discharge.
	All other domestic waste	See 33 CFR part 151.

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)