

## 40 C.F.R. § 435.44

### Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30-125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT):

#### BCT Effluent Limitations

Stream	Pollutant parameter	BCT effluent limitations
Produced Water (all facilities)	Oil & Grease	The maximum for any one day shall not exceed 72 mg/l and the 30-day average shall not exceed 48 mg/l.
Drilling Fluids and Drill Cuttings and Dewatering Effluent: <sup>1</sup>		
All facilities except Cook Inlet		No discharge.
Cook Inlet:		
Water-based drilling fluids, drill cuttings, and dewatering effluent	Free Oil	No discharge. <sup>2</sup>
Non-aqueous drilling fluids and dewatering effluent		No discharge.
Drill cuttings associated with non-aqueous drilling fluids	Free Oil	No discharge. <sup>2</sup>
Well Treatment, Workover and Completion Fluids	Free Oil	No discharge. <sup>2</sup>
Produced Sand		No discharge.
Deck Drainage	Free Oil	No discharge. <sup>3</sup>
Sanitary Waste:		
Sanitary M10	Residual Chlorine	Minimum of 1 mg/l maintained as close to this concentration as possible.

Sanitary M91M	Floating Solids	No discharge.
Domestic Waste	Floating Solids and garbage	No discharge of Floating Solids or garbage.

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)