

40 C.F.R. § 471.11

Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations for the process operations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) *Rolling spent emulsions.*

Subpart A—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of lead-tin-bismuth rolled with emulsions	
Antimony	0.068	0.030
Lead	0.010	0.005
Oil and grease	0.468	0.281
TSS	0.960	0.457
pH		(1)

¹ Within the range of 7.5 to 10.0 at all times.

(b) *Rolling spent soap solutions.*

Subpart A—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pound) of lead-tin-bismuth rolled with soap solutions	
Antimony	0.125	0.055
Lead	0.019	0.009
Oil and grease	0.860	0.520
TSS	1.80	0.840

pH		(1)
----	--	-----

¹ Within the range of 7.5 to 10.0 at all times.

(c) *Drawing spent neat oils—subpart A—BPT.* There shall be no discharge of process wastewater pollutants.

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)