

40 C.F.R. § 471.13

New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards. The mass of pollutants in the lead-tin-bismuth forming operations' process wastewater shall not exceed the following values:

(a) *Rolling spent emulsions.*

Subpart A—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of lead-tin-bismuth rolled with emulsions	
Antimony	0.067	0.030
Lead	0.010	0.005
Oil and grease	0.468	0.281
TSS	0.960	0.457
pH		(1)

¹ Within the range of 7.5 to 10.0 at all times.

(b) *Rolling spent soap solutions.*

Subpart A—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of lead-tin-bismuth rolled with soap solutions	
Antimony	0.120	0.055
Lead	0.018	0.009
Oil and grease	0.860	0.520
TSS	1.80	0.840
pH		(1)

¹ Within the range of 7.5 to 10.0 at all times.

(c) *Drawing spent neat oils—subpart A—NSPS*. There shall be no discharge of process wastewater pollutants.

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)