

# 40 C.F.R. § 471.62

## Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

- (a) *Rolling spent neat oils—subpart F—BAT.* There shall be no discharge of process wastewater pollutants.
- (b) *Rolling contact cooling water.*

### Subpart F—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of titanium rolled with contact cooling water	
Cyanide	0.142	0.059
Lead	0.205	0.098
Zinc	0.713	0.298
Ammonia	65.1	28.6
Fluoride	29.1	12.90

- (c) *Drawing spent neat oils—subpart F—BAT.* There shall be no discharge of process wastewater pollutants.
- (d) *Extrusion spent neat oils—subpart F—BAT.* There shall be no discharge of process wastewater pollutants.
- (e) *Extrusion spent lubricants.*

### Subpart F—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of titanium extruded	
Cyanide	0.021	0.009
Lead	0.030	0.015

Zinc	0.105	0.044
Ammonia	9.59	4.22
Fluoride	4.28	1.90

(f) *Extrusion press hydraulic fluid leakage.*

Subpart F—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of titanium extruded	
Cyanide	0.052	0.022
Lead	0.075	0.036
Zinc	0.260	0.109
Ammonia	23.7	10.5
Fluoride	10.6	4.70

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)