

## 40 C.F.R. § 265.1034

---

### Test methods and procedures.

---

- (a) Each owner or operator subject to the provisions of this subpart shall comply with the test methods and procedures requirements provided in this section.
  - (b) When a closed-vent system is tested for compliance with no detectable emissions, as required in § 265.1033(k) of this subpart, the test shall comply with the following requirements:
    - (1) Monitoring shall comply with Reference Method 21 in 40 CFR part 60.
    - (2) The detection instrument shall meet the performance criteria of Reference Method 21.
    - (3) The instrument shall be calibrated before use on each day of its use by the procedures specified in Reference Method 21.
    - (4) Calibration gases shall be:
      - (i) Zero air (less than 10 ppm of hydrocarbon in air).
      - (ii) A mixture of methane or n-hexane and air at a concentration of approximately, but less than, 10,000 ppm methane or n-hexane.
    - (5) The background level shall be determined as set forth in Reference Method 21.
    - (6) The instrument probe shall be traversed around all potential leak interfaces as close to the interface as possible as described in Reference Method 21.
    - (7) The arithmetic difference between the maximum concentration indicated by the instrument and the background level is compared with 500 ppm for determining compliance.
  - (c) Performance tests to determine compliance with § 265.1032(a) and with the total organic compound concentration limit of § 265.1033(c) shall comply with the following:
    - (1) Performance tests to determine total organic compound concentrations and mass flow rates entering and exiting control devices shall be conducted and data reduced in accordance with the following reference methods and calculation procedures:
      - (i) Method 2 in 40 CFR part 60 for velocity and volumetric flow rate.
      - (ii) Method 18 or Method 25A in 40 CFR part 60, appendix A, for organic content. If Method 25A is used, the organic HAP used as the calibration gas must be the single organic HAP representing the largest percent by volume of the emissions. The use of Method 25A is acceptable if the response from the high-level calibration gas is at least 20 times the standard deviation of the response from the zero calibration gas when the instrument is zeroed on the most sensitive scale.
-

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)