
40 C.F.R. § 65.150

Absorbers used as control devices.

(a) *Absorber equipment and operating requirements.* (1) Owners or operators using absorbers to meet the 98 weight-percent emission reduction or 20 parts per million by volume outlet concentration requirements as specified in § 65.63(a)(2), or 40 CFR 60.562-1(a)(1)(i)(A) for process vents, or § 65.83(a)(1) for high-throughput transfer racks, as applicable, shall meet the requirements of this section.

(2) Absorbers used to comply with the provisions of this subpart shall be operated at all times when emissions are vented to them.

(b) *Absorber performance test requirements.* (1) Unless an initial performance test was previously conducted and submitted under the referencing subpart and except as specified in § 65.157(b), the owner or operator shall conduct an initial performance test of any absorber used as a control device to comply with the provisions of this subpart according to the procedures in §§ 65.157 and 65.158. Performance test records shall be kept as specified in § 65.160(a) and (b), and a performance test report shall be submitted as specified in § 65.164. As provided in § 65.145(b)(1), a performance test may be used as an alternative to the design evaluation for storage vessels and low-throughput transfer rack controls. As provided in § 65.146(b), no performance test is required to demonstrate compliance for equipment leaks.

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)