
40 C.F.R. § 63.1108

Compliance with standards and operation and maintenance requirements.

(a) *Requirements.* The requirements of paragraphs (a)(1), (2), and (5) of this section apply to all affected sources except acrylic and modacrylic fiber production affected sources and polycarbonate production affected sources, and beginning no later than the compliance dates specified in § 63.1102(c) for ethylene production affected sources, specified in § 63.1102(d) for cyanide chemicals manufacturing affected sources, and specified in § 63.1102(e) for carbon black production affected sources. The requirements of paragraph (a)(4) of this section apply only to acrylic and modacrylic fiber production affected sources, polycarbonate production affected sources and beginning no later than the compliance dates specified in § 63.1102(c) for ethylene production affected sources, specified in § 63.1102(d) for cyanide chemicals manufacturing affected sources, and specified in § 63.1102(e) for carbon black production affected sources. The requirements of paragraphs (a)(3), (6), and (7) of this section apply to all affected sources.

(1) Except as provided in paragraph (a)(2) of this section, the emission limitations and established parameter ranges of this part shall apply at all times except during periods of startup, shutdown, malfunction, or non-operation of the affected source (or specific portion thereof) resulting in cessation of the emissions to which this subpart applies. However, if a startup, shutdown, malfunction or period of non-operation of one portion of an affected source does not affect the ability of a particular emission point to comply with the specific provisions to which it is subject, then that emission point shall still be required to comply with the applicable provisions of this subpart and any of the subparts that are referenced by this subpart during startup, shutdown, malfunction, or period of non-operation.

(2) If equipment leak requirements are referenced by this subpart for a subject source category, such requirements shall apply at all times except during periods of startup, shutdown, or malfunction, process unit shutdown (as defined in § 63.1101), or non-operation of the affected source (or specific portion thereof) in which the lines are drained and depressurized resulting in cessation of the emissions to which the equipment leak requirements apply.

(3) For batch unit operations, shutdown does not include the normal periods between batch cycles; and startup does not include the recharging of batch unit operations, or the transitional conditions due to changes in product.

(4)

(i) For acrylic and modacrylic fiber production affected sources and polycarbonate production affected sources, and beginning no later than the compliance dates specified in § 63.1102(c) for ethylene production affected sources, specified in § 63.1102(d) for cyanide chemicals manufacturing, and specified in § 63.1102(e) for carbon black production affected sources, the emission limitations and established parameter ranges of this part shall apply at all times except during periods of non-operation of the affected source (or specific portion thereof) resulting in cessation of the emissions to which this subpart applies. Equipment leak requirements shall apply at

all times except during periods of non-operation of the affected source (or specific portion thereof) in which the lines are drained and depressurized resulting in cessation of the emissions to which the equipment leak requirements apply.

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)