
40 C.F.R. § 63.323

Test methods and monitoring.

(a) When a refrigerated condenser is used to comply with § 63.322(a)(1) or (b)(1):

(1) The owner or operator shall monitor on a weekly basis the parameters in either paragraph (a)(1)(i) or (ii) of this section.

(i) The refrigeration system high pressure and low pressure during the drying phase to determine if they are in the range specified in the manufacturer's operating instructions.

(ii) The temperature of the air-perchloroethylene gas-vapor stream on the outlet side of the refrigerated condenser on a dry-to-dry machine, dryer, or reclaimer with a temperature sensor to determine if it is equal to or less than 7.2 °C (45 °F) before the end of the cool-down or drying cycle while the gas-vapor stream is flowing through the condenser. The temperature sensor shall be used according to the manufacturer's instructions and shall be designed to measure a temperature of 7.2 °C (45 °F) to an accuracy of ±1.1 °C (±2 °F).

(2) The owner or operator shall calculate the difference between the temperature of the air-perchloroethylene gas-vapor stream entering the refrigerated condenser on a washer and the temperature of the air-perchloroethylene gas-vapor stream exiting the refrigerated condenser on the washer weekly to determine that the difference is greater than or equal to 11.1 °C (20 °F).

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)