

40 C.F.R. § 63.3370

How do I demonstrate compliance with the emission standards?

You must demonstrate compliance each month with the emission limitations in § 63.3320(b)(1) through (4). For each monthly demonstration, you may apply any combination of the emission limitations to each of your web coating lines individually, to each of one or more groupings of your lines (including a single grouping encompassing all lines of your affected source), or to any combination of individual and grouped lines, so long as each web coating line is included in the compliance demonstration for the month (*i.e.*, you are not required to apply the same emission limitation to each of the individual lines or groups of lines). You may change the emission limitation that you apply each month to your individual or grouped lines, and you may change line groupings for your monthly compliance demonstration.

(a) A summary of how you must demonstrate compliance follows:

If you choose to demonstrate compliance by:	Then you must demonstrate that:	To accomplish this:
(1) Use of “as-purchased” compliant coating materials	(i) Each coating material used at an existing affected source does not exceed 0.04 kg organic HAP per kg coating material, and each coating material used at a new affected source does not exceed 0.016 kg organic HAP per kg coating material as-purchased; or	Follow the procedures set out in § 63.3370(b).
	(ii) Each coating material used at an existing affected source does not exceed 0.2 kg organic HAP per kg coating solids, and each coating material used at a new affected source does not exceed 0.08 kg organic HAP per kg coating solids as-purchased	Follow the procedures set out in § 63.3370(b).
(2) Use of “as-applied” compliant coating materials	(i) Each coating material used at an existing affected source does not exceed 0.04 kg organic HAP per kg coating material, and each coating material used at a new affected source does not exceed 0.016 kg organic HAP per kg coating material as-applied; or	Follow the procedures set out in § 63.3370(c)(1). Use either Equation 4 or 5 of § 63.3370 to determine compliance with § 63.3320(b)(2) in accordance with § 63.3370(c)(5)(i).

	(ii) Each coating material used at an existing affected source does not exceed 0.2 kg organic HAP per kg coating solids, and each coating material used at a new affected source does not exceed 0.08 kg organic HAP per kg coating solids as-applied; or	Follow the procedures set out in § 63.3370(c)(2). Use Equations 6 and 7 of § 63.3370 to determine compliance with § 63.3320(b)(3) in accordance with § 63.3370(c)(5)(i).
	(iii) Monthly average of all coating materials used at an existing affected source does not exceed 0.04 kg organic HAP per kg coating material, and monthly average of all coating materials used at a new affected source does not exceed 0.016 kg organic HAP per kg coating material as-applied on a monthly average basis; or	Follow the procedures set out in § 63.3370(c)(3). Use Equation 8 of § 63.3370 to determine compliance with § 63.3320(b)(2) in accordance with § 63.3370(c)(5)(ii).
	(iv) Monthly average of all coating materials used at an existing affected source does not exceed 0.2 kg organic HAP per kg coating solids, and monthly average of all coating materials used at a new affected source does not exceed 0.08 kg organic HAP per kg coating solids as-applied on a monthly average basis	Follow the procedures set out in § 63.3370(c)(4). Use Equation 9 of § 63.3370 to determine compliance with § 63.3320(b)(3) in accordance with § 63.3370(c)(5)(ii).
(3) Tracking total monthly organic HAP applied	Total monthly organic HAP applied does not exceed the calculated limit based on emission limitations	Follow the procedures set out in § 63.3370(d). Show that total monthly HAP applied (Equation 10 of § 63.3370) is less than the calculated equivalent allowable organic HAP (Equation 17 or 18 of § 63.3370).
(4) Accounting for volatile matter retained in the coated web or otherwise not emitted	A site- and product-specific emission factor was appropriately established for the group of products for which the site- and product-specific emission factor was used in the compliance calculations	Follow the procedures set out in § 63.3360(g) and § 63.3370(e)
(5) Use of a capture system and control device	(i) Overall organic HAP control efficiency is equal to 95 percent at an existing affected source and 98 percent at a new affected source on a monthly basis; or oxidizer outlet organic HAP concentration is no greater than 20 ppmv and capture efficiency is 100 percent; or operating parameters are continuously monitored; or	Follow the procedures set out in § 63.3370(f) to determine compliance with § 63.3320(b)(1) according to § 63.3370(j) if using a solvent recovery device, or § 63.3370(k) if using a control device and CPMS, or § 63.3370(l) if using an oxidizer.
	(ii) Overall organic HAP emission rate does not exceed 0.2 kg organic HAP per kg coating solids for an existing affected source or 0.08 kg organic HAP per kg coating solids for a new affected source on a monthly average as-applied basis;	Follow the procedures set out in § 63.3370(g) to determine compliance with § 63.3320(b)(3) according to § 63.3370(j) if using a solvent recovery device, or § 63.3370(l) if using an oxidizer.

	(iii) Overall organic HAP emission rate does not exceed 0.04 kg organic HAP per kg coating material for an existing affected source or 0.016 kg organic HAP per kg coating material for a new affected source on a monthly average as-applied basis; or	Follow the procedures set out in § 63.3370(h) to determine compliance with § 63.3320(b)(2) according to § 63.3370(j) if using a solvent recovery device, or § 63.3370(l) if using an oxidizer.
	(iv) Overall organic HAP emission rate does not exceed the calculated limit based on emission limitations	Follow the procedures set out in § 63.3370(i). Show that the monthly organic HAP emission rate is less than the calculated equivalent allowable organic HAP emission rate (Equation 17 or 18 of § 63.3370). Calculate the monthly organic HAP emission rate according to § 63.3370(j) if using a solvent recovery device, or § 63.3370(l) if using an oxidizer.
(6) Use of multiple capture and/or control devices	(i) Overall organic HAP control efficiency is equal to 95 percent at an existing affected source and 98 percent at a new affected source on a monthly basis; or	Follow the procedures set out in § 63.3370(f) to determine compliance with § 63.3320(b)(1) according to § 63.3370(f)(1) or (2).
	(ii) Average equivalent organic HAP emission rate does not exceed 0.2 kg organic HAP per kg coating solids for an existing affected source or 0.08 kg organic HAP per kg coating solids for a new affected source on a monthly average as-applied basis; or	Follow the procedures set out in § 63.3370(g) to determine compliance with § 63.3320(b)(3) according to § 63.3370(o).
	(iii) Average equivalent organic HAP emission rate does not exceed 0.04 kg organic HAP per kg coating material for an existing affected source or 0.016 kg organic HAP per kg coating material for a new affected source on a monthly average as-applied basis; or	Follow the procedures set out in § 63.3370(h) to determine compliance with § 63.3320(b)(2) according to § 63.3370(o).
	(iv) Average equivalent organic HAP emission rate does not exceed the calculated limit based on emission limitations	Follow the procedures set out in § 63.3370(i). Show that the monthly organic HAP emission rate is less than the calculated equivalent allowable organic HAP emission rate (Equation 17 or 18 of § 63.3370) according to § 63.3370(o).
(7) Use of a combination of compliant coatings and control devices	(i) Average equivalent organic HAP emission rate does not exceed 0.2 kg organic HAP per kg coating solids for an existing affected source or 0.08 kg organic HAP per kg coating solids for a new affected source on a monthly average as-applied basis; or	Follow the procedures set out in § 63.3370(g) to determine compliance with § 63.3320(b)(3) according to § 63.3370(o).
	(ii) Average equivalent organic HAP emission rate does not exceed 0.04 kg organic HAP per kg coating material for an existing affected source or 0.016 kg organic HAP per kg coating material for a new affected source on a monthly average as-applied basis; or	Follow the procedures set out in § 63.3370(h) to determine compliance with § 63.3320(b)(2) according to § 63.3370(o).

	(iii) Average equivalent organic HAP emission rate does not exceed the calculated limit based on emission limitations	Follow the procedures set out in § 63.3370(i). Show that the monthly organic HAP emission rate is less than the calculated equivalent allowable organic HAP emission rate (Equation 17 or 18 of § 63.3370) according to § 63.3370(o).
(8) Use of non-HAP coatings	All coatings for all coating lines at an affected source have organic HAP contents below 0.1 percent by mass for OSHA-defined carcinogens as specified in section A.6.4 of appendix A to 29 CFR 1910.1200, and below 1.0 percent by mass for other organic HAP compounds	Follow the procedures set out in § 63.3370(s).

(b) *As-purchased “compliant” coating materials.* (1) If you comply by using coating materials that individually meet the emission standards in § 63.3320(b)(2) or (3), you must demonstrate that each coating material applied during the month at an existing affected source contains no more than 0.04 mass fraction organic HAP or 0.2 kg organic HAP per kg coating solids, and that each coating material applied during the month at a new affected source contains no more than 0.016 mass fraction organic HAP or 0.08 kg organic HAP per kg coating solids on an as-purchased basis as determined in accordance with § 63.3360(c).

(2) You are in compliance with emission standards in § 63.3320(b)(2) and (3) if each coating material applied at an existing affected source is applied as-purchased and contains no more than 0.04 kg organic HAP per kg coating material or 0.2 kg organic HAP per kg coating solids, and each coating material applied at a new affected source is applied as-purchased and contains no more than 0.016 kg organic HAP per kg coating material or 0.08 kg organic HAP per kg coating solids.

(c) *As-applied “compliant” coating materials.* If you comply by using coating materials that meet the emission standards in § 63.3320(b)(2) or (3) as-applied, you must demonstrate compliance by following one of the procedures in paragraphs (c)(1) through (4) of this section. Compliance is determined in accordance with paragraph (c)(5) of this section.

(1) *Each coating material as-applied meets the mass fraction of coating material standard (§ 63.3320(b)(2)).* You must demonstrate that each coating material applied at an existing affected source during the month contains no more than 0.04 kg organic HAP per kg coating material applied, and each coating material applied at a new affected source contains no more than 0.016 kg organic HAP per kg coating material applied as determined in accordance with paragraphs (c)(1)(i) and (ii) of this section. You must calculate the as-applied organic HAP content of as-purchased coating materials which are reduced, thinned, or diluted prior to application.

(i) Determine the organic HAP content or volatile organic content of each coating material applied on an as-purchased basis in accordance with § 63.3360(c).

(ii) Calculate the as-applied organic HAP content of each coating material using Equation 4:

$$C_{ahi} = \frac{\left(C_{hi}M_i + \sum_{j=1}^n C_{hj}M_j \right)}{M_i + \sum_{j=1}^n M_j}$$

Equation 4

Where:

C_{ahi} = Monthly average, as-applied, organic HAP content of coating material, i, expressed as a mass fraction,

kg/kg. C_{hi} = Organic HAP content of coating material, i, as-purchased, expressed as a mass fraction, kg/kg. M_i = Mass of as-purchased coating material, i, applied in a month, kg. q = number of different materials added to the coating material. C_{hij} = Organic HAP content of material, j, added to as-purchased coating material, i, expressed as a mass fraction, kg/kg. M_{ij} = Mass of material, j, added to as-purchased coating material, i, in a month, kg. or calculate the as-applied volatile organic content of each coating material using Equation 5:

$$C_{avi} = \frac{\left(C_{vi}M_i + \sum_{j=1}^q C_{vij}M_{ij} \right)}{M_i + \sum_{j=1}^q M_{ij}}$$

Equation 5

Where:

C_{avi} = Monthly average, as-applied, volatile organic content of coating material, i, expressed as a mass fraction, kg/kg. C_{vi} = Volatile organic content of coating material, i, expressed as a mass fraction, kg/kg. M_i = Mass of as-purchased coating material, i, applied in a month, kg. q = Number of different materials added to the coating material. C_{vij} = Volatile organic content of material, j, added to as-purchased coating material, i, expressed as a mass fraction, kg/kg. M_{ij} = Mass of material, j, added to as-purchased coating material, i, in a month, kg.

(2) Each coating material as-applied meets the mass fraction of coating solids standard (§ 63.3320(b)(3)). You must demonstrate that each coating material applied at an existing affected source contains no more than 0.20 kg of organic HAP per kg of coating solids applied and each coating material applied at a new affected source contains no more than 0.08 kg of organic HAP per kg of coating solids applied. You must demonstrate compliance in accordance with paragraphs (c)(2)(i) and (ii) of this section.

(i) Determine the as-applied coating solids content of each coating material following the procedure in § 63.3360(d). You must calculate the as-applied coating solids content of coating materials which are reduced, thinned, or diluted prior to application, using Equation 6:

$$C_{si} = \frac{\left(C_{si}M_i + \sum_{j=1}^q C_{sij}M_{ij} \right)}{M_i + \sum_{j=1}^q M_{ij}}$$

Equation 6

Where:

C_{si} = Coating solids content of coating material, i, expressed as a mass fraction, kg/kg. M_i = Mass of as-purchased coating material, i, applied in a month, kg. q = Number of different materials added to the coating material. C_{sij} = Coating solids content of material, j, added to as-purchased coating material, i, expressed as a mass-fraction, kg/kg. M_{ij} = Mass of material, j, added to as-purchased coating material, i, in a month, kg.

(ii) Calculate the as-applied organic HAP to coating solids ratio using Equation 7:

$$H_{ai} = \frac{C_{ahi}}{C_{si}}$$

Equation 7

Where:

H_{si} = As-applied, organic HAP to coating solids ratio of coating material, i. C_{ahi} = Monthly average, as-applied,

organic HAP content of coating material, i , expressed as a mass fraction, kg/kg. C_{asi} = Monthly average, as-applied, coating solids content of coating material, i , expressed as a mass fraction, kg/kg.

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)