

40 C.F.R. § 63.363

Compliance and performance provisions.

- (a) Continuous compliance. You must demonstrate continuous compliance with the applicable emission standard(s) using an EtO CEMS, including a shared EtO CEMS, installed and operated in accordance with the requirements of Performance Specification 19 in appendix B and Procedure 7 in appendix F to part 60 of this chapter. Alternatively, if you own or operate a facility where EtO use is less than 100 pounds/yr, you may demonstrate continuous compliance by conducting annual performance tests using the performance testing requirements in § 63.7, according to the applicability in table 6 to this subpart, the procedures listed in this section, and the test methods listed in § 63.365. If you elect to demonstrate compliance through periodic performance testing, you must also demonstrate continuous compliance with each operating limit required under this section according to the methods specified in § 63.364. If you own or operate an area source facility where EtO use is less than 100 pounds/yr where an existing collection of Group 2 room air emission is operated in accordance with the PTE requirements of EPA Method 204 of appendix M to part 51 of this chapter, you may instead conduct these performance tests once every three years.
- (b) Initial compliance for Facilities that use EtO CEMS. To demonstrate initial compliance with an emission standard using a CEMS that measures HAP concentrations directly (i.e., an EtO CEMS), the initial performance test must consist of the first 30 operating days after the certification of the CEMS according to Performance Specification 19 in Appendix B to part 40 of this chapter. The initial compliance demonstration period must be completed on or before the date that compliance must be demonstrated (i.e., 180 days after the applicable compliance date). You must follow the procedures in appendix A to this subpart.

This document is only available to subscribers. Please log in or purchase access.

Purchase Login