
40 C.F.R. § 63.843

Emission limits for existing sources.

(a) *Potlines*. The owner or operator shall not discharge or cause to be discharged into the atmosphere any emissions of TF, POM, PM, nickel, arsenic or PCB in excess of the applicable limits in paragraphs (a)(1) through (6) of this section.

(1) *TF limits*. Emissions of TF shall not exceed:

- (i) 0.95 kg/Mg (1.9 lb/ton) of aluminum produced for each CWPB1 potline;
- (ii) 1.5 kg/Mg (3.0 lb/ton) of aluminum produced for each CWPB2 potline;
- (iii) 1.25 kg/Mg (2.5 lb/ton) of aluminum produced for each CWPB3 potline;
- (iv) 0.8 kg/Mg (1.6 lb/ton) of aluminum produced for each SWPB potline; and
- (v) [Reserved]
- (vi) 1.35 kg/Mg (2.7 lb/ton) of aluminum produced for each VSS2 potline.

(2) *POM limits*. Emissions of POM shall not exceed:

- (i)
- (ii) [Reserved]
- (iii) 0.85 kg/Mg (1.9 lb/ton) of aluminum produced for each VSS2 potline;
- (iv) 0.55 kg/Mg (1.1 lb/ton) of aluminum produced for each CWPB1 prebake potline;
- (v) 6.0 kg/Mg (12 lb/ton) of aluminum produced for each CWPB2 prebake potline;
- (vi) 1.4 kg/Mg (2.7 lb/ton) of aluminum produced for each CWPB3 prebake potline; and

This document is only available to subscribers. Please log in or purchase access.

[Purchase Login](#)