
40 C.F.R. § 60.372a

Standards for lead.

(a) On and after the date on which the performance test required to be conducted by § 60.8 is completed, no owner or operator subject to the provisions of this subpart may cause the emissions listed in paragraphs (a)(1) through (8) of this section to be discharged into the atmosphere. The emission limitations and opacity limitations listed in paragraphs (a)(1) through (8) of this section apply at all times, including periods of startup, shutdown and malfunction. As provided in § 60.11(f), this paragraph (a) supersedes the exemptions for periods of startup, shutdown, and malfunction in the general provisions in subpart A of this part. You must also comply with the requirements in paragraphs (b) and (c) of this section.

(1) From any grid casting facility, any gases that contain lead in excess of 0.08 milligram of lead per dry standard cubic meter of exhaust (0.000035 gr/dscf).

(2) From any paste mixing facility, any gases that contain in excess of 0.10 milligram of lead per dry standard cubic meter of exhaust (0.0000437 gr/dscf) or emit no more than 0.9 gram of lead per hour (0.002 lbs/hr) total from all paste mixing sources. If a facility is complying with the 0.9 gram of lead per hour, you must sum the emission rate from all the paste mixing sources.

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)