
40 C.F.R. § 60.275b

Test methods and procedures.

- (a) During performance tests required in §§ 60.8 and 60.272b(d), the owner or operator shall not add gaseous diluents to the effluent gas stream after the fabric filter in any pressurized fabric filter collector, unless the amount of dilution is separately determined and considered in the determination of emissions.
- (b) When emissions from any EAF(s) or AOD vessel(s) are combined with emissions from facilities not subject to the provisions of this subpart but controlled by a common capture system and control device, the owner or operator shall use any one of the following procedures during a performance test (see also § 60.276b(e)):
- (1) Determine compliance using the combined emissions.
 - (2) Use a method that is acceptable to the Administrator or delegated authority and that compensates for the emissions from the facilities not subject to the provisions of this subpart.
 - (3) Any combination of the criteria of paragraphs (b)(1) and (2) of this section.
- (c) When emission from any EAF(s) or AOD vessel(s) are combined with emissions from facilities not subject to the provisions of this subpart, compliance with § 60.272b(a)(3) will be based on emissions from only the affected facility(ies). The owner or operator may use operational knowledge to determine the facilities that are the sources, in whole or in part, of any emissions observed in demonstrations of compliance with § 60.272b(a)(3).

This document is only available to subscribers. Please [log in](#) or [purchase access](#).

[Purchase Login](#)